



<b>Health</b>	<b>3</b>
<b>Fire</b>	<b>0</b>
<b>Reactivity</b>	<b>0</b>
<b>Personal Protection</b>	

## SECTION 1 – MATERIAL IDENTIFICATION

- A) **Trade / Material Name** Two-Pack Polyurethane Coating  
 B) **Description** Finish coat for protective coating systems  
 C) **Product Code(s)** RTB-848-A  
 D) **Manufacturer Name** Ronass Chemical Producing Co.  
 E) **Manufacturer Information** #95 Ghaem Magham Avenue, Tehran, Iran  
 Tel: (+98-21) 88307248-9  
 Fax: (+98-21) 88305965  
[www.ronass.com](http://www.ronass.com) | [info@ronass.com](mailto:info@ronass.com)  
 F) **MSDS Preparation Date** July 17, 2018

## SECTION 2 – HAZARDOUS INGREDIENTS

Name	Percentage	Max. Legal Limit
Organic Solvents	Max. 30% (By Weight)	Max. 40% (By Weight)
Total Pigments	Max. 40% (By Weight)	N.A.
Solid Resins	Max. 32% (By Weight)	N.A.

## SECTION 3 – PHYSICAL DATA

- A) **Appearance and Odor** Coloured Liquid | Light Odor  
 B) **V.O.C.** Max. 25%  
 C) **Viscosity** Max. 120 KU  
 D) **pH Range** 5.8 – 7  
 E) **Water Solubility** No  
 F) **Specific Gravity** 1.40 ± 0.05 gr/cm<sup>3</sup> (Component A)  
 Silver: 1.15 ± 0.05 gr/cm<sup>3</sup> (After Mixing) | Other Colours: 1.30 ± 0.05 gr/cm<sup>3</sup> (After Mixing)  
 G) **Flash Point** 28°C  
 H) **Boiling Point** 128°C  
 I) **Melting / Freezing Point** N.A.

## SECTION 4 – STABILITY AND REACTIVITY DATA

**MATERIAL IS STABLE | HAZARDOUS POLYMERIZATION CANNOT OCCUR**

- |  |   |
|--|---|
| A) Chemical Incompatibilities          | Water, oil and inorganic compounds  |
| B) Conditions to Avoid                 | Excessive heat, sparks, open flame, high voltage power lines / switchboards |
| C) Hazardous Decomposition Product(s)  | Carbon Monoxide, Carbon Dioxide, Organic Solvent Vapor                      |
| D) Hazardous Polymerization Product(s) | None  |

## SECTION 5 – LEAK AND DISPOSAL PROCEDURES

- |                                   |   |
|-----------------------------------|---|
| A) Spill and / or Leak Procedures | Contain and collect with absorbent material   |
| B) Waste Management / Disposal    | In accordance with state and provincial regulations   |
| C) Large Spills                   | Remove all sources of ignition; ventilate area; Contain spill with inert absorbent, or mop up |

## SECTION 6 – FIRST AID MEASURES

**THIS PRODUCT IS NOT CONSIDERED A CARCINOGEN BY OSHA, NTP, IARC**

- |   |   |
|---|---|
| A) Summary of Risks                                     | Contact may cause eye irritation; prolonged contact with skin can cause irritation; excessive inhalation can cause dizziness and headache |
| B) Medical Conditions That May Be Aggravated by Contact | Pre-existing disorders of the liver or kidneys, eyes, skin, or respiratory system may be aggravated by exposure to this product           |
| C) Primary Entry Route(s)                               | Eye contact; skin contact; respiratory and ingestion systems  |
| D) Acute Effect(s)                                      | Eye and skin irritation; dizziness; headache and nausea from excessive inhalation   |
| E) Chronic Effect(s)                                    | Aspiration of product into lungs (due to vomiting) can cause chemical pneumonitis, which can be fatal                                     |
| F) Signs and Symptoms of Overexposure                   |   |
| ❖ Eye Contact   | Redness; tearing; blurred vision  |
| ❖ Skin Contact  | Redness; blistering   |
| ❖ Inhalation  | Dizziness; headache   |
| ❖ Ingestion   | Nausea; cramps; diarrhea  |
| G) First Aid  |   |
| ❖ Eye Contact   | Flush with plenty water for 10 minutes; get medical advice  |
| ❖ Skin Contact  | Wash with soap and cool water; seek medical attention if irritation persists  |
| ❖ Inhalation  | Move to an area with fresh air  |
| ❖ Ingestion   | Do not induce vomiting; call a physician immediately for instructions   |



